a NEWMACHINE release from UNION SPECIAL

The Union Special Packaging Division announces the next generation of 56100 bag seaming machines

—the new white "B" Series—is now released for sale



These new white 56100s are distinguished from their predecessors by a new bearing for the left mainshaft. This replaces the bushing used in earlier styles. The bearing handles the load stress at that crucial point much more effectively than a bushing. The bearing allows the shaft to run smoother and cooler. No more downtime or repair labor due to a burned up bushing!

Another benefit of the new bearing will be seen by customers running the new machines in high duty cycle applications: production can increase because machine

speed in those situations may be increased by 500 to 1000RPM.

These new white 56100s are designated with the letter "B" at the end of the style, for example, 56100MB, 56100RB, etc.





56100 Specifications		STITCH	SEWING	MAXIMUM
STYLE & APPLICATION	SEAM	LENGTH	CAPACITY	RPM
56100MB—for seaming bags made of cotton, light to medium weight burlap, paper, jute, or woven poly. Can be fitted with optional turned up hemmer or double-edge folder if desired, for additional operations.	401SSa-1	3.6–7.2mm 3.5–7 SPI	up to 8mm 5/16"	6000
56100MZ35B—similar to 56100MB, except with synchronizer handwheel pulley.	401SSa-1	3.6-7.2mm 3.5-7 SPI	up to 8mm 5/16"	6000
56100MZ3B—similar to 56100MB, except sews 101 stitch. For seaming bags.	101SSa-1	3.6-7.2mm 3.5-7 SPI	up to 8mm 5/16"	5000
56100PB—similar to MB, except with high needle throw, split-toe presser foot and wider feed parts for seaming medium to extra-heavy weight bags.	401SSa-1	3.6–7.2mm 3.5–7 SPI	up to 11mm 7/16"	5500
56100TB—for hemming openings, or making double turned-in side and bottom seams on burlap, paper, jute, or woven poly bags. Also for sewing spouts on FIBCs. Turned up hemmer adjusts from 10 to 15mm, capacity from 2 to 4mm.	401EFb-1	3.6-7.2mm 3.5-7 SPI	up to 8mm 5/16"	5500
56100MZ27B—similar to 56100TB, without hemmer.	401SSa-1	3.6-7.2mm 3.5-7 SPI	up to 8mm 5/16"	5000
56100MZ34B—similar to 56100MZ27B, except for use on automated equipment.	401SSa-1	3.6-7.2mm 3.5-7 SPI	up to 8mm 5/16"	5000
56100SAB—for seaming heavy multi-wall paper bags with a 401 stitch. Presser foot has filler cord guide.	401SSa-1	3.6-7.2mm 3.5-7 SPI	up to 6mm 15/64"	4300
56100RB—for seaming heavy multi-wall paper bags with a 101 stitch. Presser foot has filler cord guide and tape slot.	101SSa-1	3.6–7.2mm 3.5–7 SPI	up to 6mm 15/64"	4500
56100RAB— similar to 56100RB, except without covers or thread stand, for use in automated bag sewing systems.	101SSa-1	3.6–7.2mm 3.5–7 SPI	up to 6mm 15/64"	4300

56100 Sp	oare Parts						
NEW	REPLACES	PRESSER FOOT	THROAT PLATE	LOWER FEED	UPPER FEED	EDGE GUIDE	HEMMER
56100MB	56100M	43120	C51124D	51105G	_	24X	_
56100MZ35B	56100MZ35	43120	C51124D	51105G	_	24X	_
56100MZ3B	56100MZ3	43120	A10804	1805A	_	_	_
56100PB	56100P	G198X	6624L	6605L	_	24X	_
56100TB	56100T	G198X	195X	6605L	_	_	A9795
56100MZ27B	56100MZ27	G198X	195X	6605L	_	24X	
56100MZ34B	56100MZ34	G198X	195X	6605L	_	24X	
56100SAB	56100Z28B	51120X	51124M	C51105P	C51126M	_	_
56100RB	56100Z30B	51120Q	51124M	C51105N	C51126H	_	_
56100RAB	56100Z31B	51120Q	51124M	C51105N	C51126H	_	_